

單相馬達 / Single Phase AC IP55 50Hz/60Hz

型號 Model	曲線編號 Curve No.	頻率 Frequency (Hz)	功率 Output (kW)	電壓 Voltage (V)	滿載額定電流 Current (A)	靜壓 吸Vacuum / 吐Compressor (mbar)	最大風量 Max Airflow (m ³ /min)	噪音 Noise (dB)A	重量 Weight (Kg)
DG-100-11	D1	50	0.18	100-120/200-240	2.50/1.25	50/40	1.0	52	6.5
	G1	60	0.2	110-120/220-240	2.60/1.30	70/70	1.2	55	
DG-200-11	D2	50	0.4	100-120/200-240	5.40/2.70	110/130	1.5	58	11.5
	G2	60	0.5	110-120/220-240	7.80/3.90	130/150	1.8	61	
DG-200-11W	D3	50	0.4	100-120/200-240	5.80/2.90	110/130	1.5	58	12
	G3	60	0.5	110-120/220-240	7.80/3.90	130/150	1.8	61	
DG-300-11	D4	50	0.75	100-120/200-240	11.6/5.80	140/150	2.6	63	16
	G4	60	0.85	110-120/220-240	13.0/6.50	140/140	3.1	64	
DG-300-11W	D5	50	0.75	100-120/200-240	11.6/5.80	140/150	2.5	63	16.5
	G5	60	0.85	110-120/220-240	13.0/6.50	140/140	3.1	64	
DG-300-31	D6	50	1.1	100-120/200-240	14.0/7.00	160/190	2.6	63	16.5
	G6	60	1.3	110-120/220-240	16.0/8.00	180/190	3.1	64	
DG-400-21	D7	50	1.1	100-120/200-240	15.8/7.70	150/150	3.7	70	23.5
	G7	60	1.3	110-120/220-240	19.2/9.60	150/140	4.4	73	
DG-400-31	D8	50	1.5	100-120/200-240	20.0/10.0	180/190	3.7	70	26
	G8	60	1.75	110-120/220-240	22.8/11.4	180/170	4.4	73	
DG-400-31W	D9	50	1.5	100-120/200-240	20.0/10.0	180/190	3.7	70	26.5
	G9	60	1.75	110-120/220-240	22.8/11.4	180/170	4.4	73	
DG-230-11	D10	50	0.75	100-120/200-240	9.20/4.50	180/220	1.6	60	17.5
	G10	60	0.85	110-120/220-240	11.0/5.40	200/220	1.8	66	
DG-330-11	D11	50	1.5	100-120/200-240	20.0/10.0	240/250	2.6	66	28.5
	G11	60	1.75	110-120/220-240	22.8/11.4	250/260	3.1	69	

附註 / Remark :

- 上述資料供參考，如有不同以實品為主。
Information above is for reference, product only when different.
- 本公司保有設計變更之權利，恕不另行通知。
We reserve the right to change the design without notice.
- 如有任何疑問請洽經銷商或本公司。
Should you require any further information or assistance, please do not hesitate to contact us or distributors.



型號說明 Description of model
DG- XXX -xx
系列代號 / Series number

DG-xxx- X x
代表各系列中功率大小排序 The sort of output in each series

DG-xxx-x X
代表電壓 / Voltage Code

電壓代碼	50Hz	60Hz
Voltage Code		
0 :	1~ 100-120V	110-120V
1 :	1~ 100-120/200-240V	110-120/220-240V
2 :	1~ 185-220V	200-240V
3 :	1~ 200-220V	220-240V
4 :	3~ 200-240V Δ	200-240V Δ
5 :	3~ 185-225 Δ/320-390Y	200-240 Δ/345-415Y
6 :	3~ 200-240 Δ/345-415Y	220-275 Δ/380-480Y
7 :	特殊電壓	
8 :	3~ 345-415 Δ/600-720Y	380-480 Δ/660-830Y
9 :	3~ 400-460 Δ/690-790Y	415-500 Δ/720-860Y

DG-xxx-xxW	耐水氣及吸熱風型 Waterproof
B	低風壓 Low Pressure
L	左盒 Terminal box on the left
R	右盒 Terminal box on the right

50Hz/60Hz 單相曲線圖 / Single Phase Curve

