

三相馬達 / Three Phase AC IP55 50Hz

型號 Model	曲線 編號 Curve No.	頻率 Frequency (Hz)	功率 Output (kW)	電壓 Voltage (V)	滿載額定電流 Current (A)	靜壓 Static pressure Vacuum / Compressor (mbar)	最大風量 Max Airflow (m ³ /min)	噪音 Noise (dB)A	重量 Weight (Kg)
DG-100-16	D12	50	0.18	200-240 Δ/345-415Y	1.10 Δ/0.64Y	50/60	1	52	6.5
DG-200-16	D13	50	0.4	200-240 Δ/345-415Y	2.20 Δ/1.30Y	110/130	1.5	58	10.5
DG-200-16W	D14	50	0.4	200-240 Δ/345-415Y	2.20 Δ/1.30Y	100/130	1.5	58	11
DG-300-16	D15	50	0.75	200-240 Δ/345-415Y	3.70 Δ/2.14Y	140/140	2.6	63	14
DG-300-26	D16	50	0.9	200-240 Δ/345-415Y	4.20 Δ/2.40Y	165/180	2.6	63	15
DG-300-16B	D17	50	0.75	200-240 Δ/345-415Y	3.70 Δ/2.14Y	110/120	2.6	63	14
DG-300-16W	D18	50	0.75	200-240 Δ/345-415Y	3.70 Δ/2.14Y	140/140	2.6	63	14.5
DG-300-36	D19	50	1.3	200-240 Δ/345-415Y	4.60 Δ/2.65Y	175/200	2.6	63	16
DG-400-16	D20	50	0.9	200-240 Δ/345-415Y	4.20 Δ/2.40Y	130/120	3.7	70	20.5
DG-400-26	D21	50	1.3	200-240 Δ/345-415Y	5.70 Δ/3.30Y	180/180	3.7	70	22
DG-400-36	D22	50	1.75	200-240 Δ/345-415Y	6.70 Δ/3.90Y	210/220	3.7	70	23
DG-400-36B	D23	50	1.75	200-240 Δ/345-415Y	6.70 Δ/3.90Y	140/160	3.7	70	23
DG-400-36W	D24	50	1.75	200-240 Δ/345-415Y	6.70 Δ/3.90Y	210/220	3.7	70	23.5
DG-400-46	D25	50	2.2	200-240 Δ/345-415Y	7.80 Δ/4.50Y	220/270	3.7	70	26
DG-600-16	D26	50	2.2	200-240 Δ/345-415Y	9.70 Δ/5.60Y	220/210	5.5	72	32
DG-600-16B	D27	50	2.2	200-240 Δ/345-415Y	9.70 Δ/5.60Y	160/200	5.5	72	32
DG-600-16W	D28	50	2.2	200-240 Δ/345-415Y	9.70 Δ/5.60Y	220/210	5.5	72	32.5
DG-600-26	D29	50	3.4	200-240 Δ/345-415Y	12.5 Δ/7.20Y	255/270	5.5	72	34
DG-600-26W	D30	50	3.4	200-240 Δ/345-415Y	12.5 Δ/7.20Y	255/270	5.5	72	35.5
DG-600-36	D31	50	4	200-240 Δ/345-415Y	14.3 Δ/8.20Y	270/320	5.5	72	37
DG-800-16	D32	50	5.5	200-240 Δ/345-415Y	25.3 Δ/14.6Y	270/290	9.5	74	77
DG-800-26	D33	50	7.5	200-240 Δ/345-415Y	31.5 Δ/18.2Y	295/390	9.5	74	88
DG-900-16	D34	50	9	200-240 Δ/345-415Y	36.0 Δ/20.8Y	200/190	18.9	76	100
DG-900-26	D35	50	13	200-240 Δ/345-415Y	46.8 Δ/27.0Y	290/270	18.9	76	112
DG-900-36	D36	50	20	200-240 Δ/345-415Y	66.7 Δ/38.6Y	350/440	18.9	76	159
DG-230-16	D37	50	0.75	200-240 Δ/345-415Y	3.45 Δ/2.00Y	200/240	1.6	60	17
DG-330-16	D38	50	1.75	200-240 Δ/345-415Y	6.70 Δ/3.90Y	275/300	2.6	66	25
DG-330-26	D39	50	2.2	200-240 Δ/345-415Y	7.80 Δ/4.50Y	320/390	2.6	66	28
DG-430-16	D40	50	3.4	200-240 Δ/345-415Y	12.5 Δ/7.20Y	345/410	3.7	74	40
DG-430-26	D41	50	4	200-240 Δ/345-415Y	14.3 Δ/8.20Y	355/460	3.7	74	43
DG-630-26	D42	50	4	200-240 Δ/345-415Y	14.3 Δ/8.20Y	350/350	5.5	75	55
DG-630-36	D43	50	5.5	200-240 Δ/345-415Y	21.6 Δ/12.5Y	410/500	5.5	75	72
DG-630-46	D44	50	7.5	200-240 Δ/345-415Y	31.5 Δ/18.2Y	420/580	5.5	75	82
DG-640-36	D45	50	5.5	200-240 Δ/345-415Y	21.6 Δ/12.5Y	200/220	7.9	75	72
DG-640-46	D46	50	7.5	200-240 Δ/345-415Y	31.5 Δ/18.2Y	240/275	7.9	75	82
DG-830-16	D47	50	7.5	200-240 Δ/345-415Y	31.5 Δ/18.2Y	350/350	9.5	76	112
DG-830-26	D48	50	13	200-240 Δ/345-415Y	46.8 Δ/27.0Y	430/600	9.5	76	142
DG-830-36	D49	50	20	200-240 Δ/345-415Y	66.7 Δ/38.6Y	450/700	9.6	76	160
DG-840-16	D50	50	7.5	200-240 Δ/345-415Y	31.5 Δ/18.2Y	180/145	14.2	76	110
DG-840-26	D51	50	13	200-240 Δ/345-415Y	46.8 Δ/27.0Y	250/250	14.2	76	140
DG-840-36	D52	50	20	200-240 Δ/345-415Y	66.7 Δ/38.6Y	300/300	14.2	76	160

附註 / Remark : 1. 上述資料供參考，如有不同以實品為主。

Information above is for reference, product only when different.

2. 本公司保有設計變更之權利，恕不另行通知。

We reserve the right to change the design without notice.

3. 如有任何疑問請洽經銷商或本公司。

Should you require any further information or assistance, please do not hesitate to contact us or distributors.

50Hz 三相曲線圖 / Three Phase Curve

